



Colour:		Standard CRI 90, other RAL colours on request (please add RAL code after index number)
LED module:		Tridonic or equivalent LED module included
Colour temperature:		3000K or 4000K
Colour Rendering Index (CRI)		>80 in standard
Driver:		Electronic driver in standard, DALI on request
Emergency unit:		On request - Standard or DALI 3 hour emergency unit
Movement sensor:		on request
Daylight control sensor:		on request
Operating temperature range:		0°C ... +40°C
IP Class:		IP20 in standard, IP44 on request
Power:		220-240V 50/60Hz
Lighting direction:		Direct lighting, direct / indirect lighting
Reflector type:		Aluminium white
Light distribution:		Symmetric
Diffuser:		White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.
General data:		5 Years standard warranty
		Different lumen output or wattage available on request
		All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
		Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
		System power consumption (LED module & driver) depends on components used





Standard CRI 9000, other RAL colours on request (please add RAL code after index number)

Colour:	Osram or Tridonic LED module included		
LED module:	3000K or 4000K		
Colour temperature:	>80 in standard		
Colour Rendering Index (CRI)	Electronic integrated driver in standard, DALI on request		
Driver:	N/A		
Emergency unit:	N/A		
Movement sensor:	N/A		
Daylight control sensor:	N/A		
Operating temperature range:	0°C... +40°C		
IP Class:	IP20 in standard, IP44 on request		
Power:	220-240V 50/60Hz		
Lighting direction:	Direct lighting - index 3512.XXXX, direct / indirect lighting - index 6607.XXXX		
Reflector type:	Aluminium white		
Light distribution:	Symmetric		
Diffuser:	White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.		
General data:	5 Years standard warranty		
	Different lumen output or wattage available on request		
	All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist		
	Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.		
	System power consumption (LED module & driver) depends on components used		

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	3,00
4000	Ra > 80	50.000	5	3	3,00

3000	Ra > 80	50.000	5	3	3,00
4000	Ra > 80	50.000	5	3	3,00




[AC] diffuser



[MPR] diffuser





Standard CRI 9000, other RAL colours on request (please add RAL code after index number)

Tridonic or equivalent LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting - index 3513/4227/3514/3515, direct / Indirect - index 6608/6609/6610/6611

Aluminium white

Symmetric

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements, Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	3,70
4000	Ra > 80	50.000	5	3	3,70
3000	Ra > 80	50.000	5	3	3,70
4000	Ra > 80	50.000	5	3	3,70

PND






Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	4,30
4000	Ra > 80	50.000	5	3	4,30
3000	Ra > 80	50.000	5	3	4,30
4000	Ra > 80	50.000	5	3	4,30

PND





Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	6,90
4000	Ra > 80	50.000	5	3	6,90
3000	Ra > 80	50.000	5	3	6,90
4000	Ra > 80	50.000	5	3	6,90




Direct/indirect version

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	6,90
4000	Ra > 80	50.000	5	3	6,90

PND





[WD] diffuser

[AC] diffuser

[MPR]

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	20,00
4000	Ra > 80	50.000	5	3	20,00

3000	Ra > 80	50.000	5	3	20,00
4000	Ra > 80	50.000	5	3	20,00

PND



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	23,00
4000	Ra > 80	50.000	5	3	23,00

3000	Ra > 80	50.000	5	3	23,00
4000	Ra > 80	50.000	5	3	23,00

PND



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	30,00
4000	Ra > 80	50.000	5	3	30,00

3000	Ra > 80	50.000	5	3	30,00
4000	Ra > 80	50.000	5	3	30,00

[AC] diffuser

[MPR] diffuser

Standard Gray 9000, other RAL colours on request (please add RAL code after index number)

Tridonic or equivalent LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting - index 6612/415/6106/
direct / indirect - index 6613/6614/6615

Aluminium white

Symmetric

White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

5 Years standard warranty


Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements, Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Available luminaire versions





Colour: Standard Gray 9000, Other RAL colours on request (please add RAL code after index number)

LED module: Tridonic or equivalent LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

General data: 5 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used




MINI



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	4,00
4000	Ra > 80	50.000	5	3	4,00

MINI



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00

[AC] diffuser

[MPR] diffuser



Colour:		Standard CIE 9000, other RAL colours on request (please add RAL code after index number)
LED module:		Philips / Osram or Tridonic LED module included
Colour temperature:		3000K or 4000K
Colour Rendering Index (CRI)		>80 in standard
Driver:		Electronic driver in standard, DALI on request
Emergency unit:		On request - Standard or DALI 3 hour emergency unit
Movement sensor:		on request
Daylight control sensor:		on request
Operating temperature range:		0°C ... +40°C
IP Class:		IP20 in standard, IP44 on request
Power:		220-240V 50/60Hz
Lighting direction:		Direct lighting, direct / indirect lighting
Reflector type:		Aluminium white
Light distribution:		Symmetric
Diffuser:		White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.
General data:		5 Years standard warranty
		Different lumen output or wattage available on request
		All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
		Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
		System power consumption (LED module & driver) depends on components used



[AC] diffuser

[MPR] diffuser



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	2,00
4000	Ra > 80	50.000	5	3	2,00

ED



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	4,00
4000	Ra > 80	50.000	5	3	4,00

Colour:		Standard CRI 90,00, other RAL colours on request (please add RAL code after index number)
LED module:		Osram or equivalent LED included
Colour temperature:		3000K or 4000K
Colour Rendering Index (CRI)		>80 in standard
Driver:		Electronic driver in standard, DALI on request
Emergency unit:		N/A
Movement sensor:		N/A
Daylight control sensor:		N/A
Operating temperature range:		0°C ... +40°C
IP Class:		IP20 in standard, IP44 on request
Power:		220-240V 50/60Hz
Lighting direction:		Direct lighting
Reflector type:		Aluminium white
Light distribution:		Symmetric
Diffuser:		White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.
General data:		3 Years standard warranty
		Different lumen output or wattage available on request
		All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelst
		Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
		System power consumption (LED module & driver) depends on components used

[AC] diffuser

[MPR] diffuser



Standard Gray 3000, other RAL colours on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting - index 5966, 4230

direct / indirect lighting - index 5966 UD, 4230 UD

Aluminium white

Symmetric

White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:


Diffuser:

General data:

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	6,50
4000	Ra > 80	50.000	5	3	6,50

3000	Ra > 80	50.000	5	3	6,50
4000	Ra > 80	50.000	5	3	6,50

LED



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00

3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00

[AC] diffuser

[MPR] diffuser



Colour: Standard Gray 3000, Other RAL colours on request (please add RAL code after index number)

LED module: Philips / Osram or Tridonic LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting - index 6057, 5854
direct / Indirect lighting - index 6057, UD, 5854, UD

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

General data: 5 Years standard warranty
Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements, Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used


Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	11,00
4000	Ra > 80	50.000	5	3	11,00

3000	Ra > 80	50.000	5	3	11,00
4000	Ra > 80	50.000	5	3	11,00

3000	Ra > 80	50.000	5	3	12,00
4000	Ra > 80	50.000	5	3	12,00

3000	Ra > 80	50.000	5	3	12,00
4000	Ra > 80	50.000	5	3	12,00

LED



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	12,00
4000	Ra > 80	50.000	5	3	12,00


3000	Ra > 80	50.000	5	3	12,00
4000	Ra > 80	50.000	5	3	12,00

3000	Ra > 80	50.000	5	3	12,00
4000	Ra > 80	50.000	5	3	12,00



[AC] diffuser

[MPR] diffuser





Standard CRI 9000, other RAL colours on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting - index 5971, 4838, 5665, 5666

direct / Indirect lighting - index 5971 UD, 4838 UD, 5665 UD, 5666 UD

Aluminium white

Symmetric

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

Diffuser:

General data:

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	12,50
4000	Ra > 80	50.000	5	3	12,50

LED

IP20

Ø 1500

06

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	15,00
4000	Ra > 80	50.000	5	3	15,00

LED

IP20

Ø 2100

06

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	23,00
4000	Ra > 80	50.000	5	3	23,00

LED

IP20

Ø 2500

06

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	28,00
4000	Ra > 80	50.000	5	3	28,00


LED

IP20

Ø 2500

06

Available luminaire versions



[AC] diffuser

[WD] diffuser

Standard CRI 90,00, other RAL colours on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting - index 5425, 6022

direct / Indirect lighting - index 5425 UD, 6022 UD

Aluminium white

Symmetric

White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

Diffuser:

General data:

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	36,00
4000	Ra > 80	50.000	5	3	36,00

3000	Ra > 80	50.000	5	3	36,00
4000	Ra > 80	50.000	5	3	36,00

LED



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	55,00
4000	Ra > 80	50.000	5	3	55,00

3000	Ra > 80	50.000	5	3	55,00
4000	Ra > 80	50.000	5	3	55,00

[AC] diffuser

[MPR] diffuser





Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

Diffuser:

General data:



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	27,00
4000	Ra > 80	50.000	5	3	27,00

Standard Gray 9000, other RAL colours on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

on request

on request

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct lighting

Aluminium white

Symmetric

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.


5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

Diffuser:

General data:



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6518.14400/830	14400	120	3000	Ra > 80	50.000	5	3	30,00
6518.14400/840	14400	120	4000	Ra > 80	50.000	5	3	30,00

Colour: Standard CRI 90,00, other RAL colours on request (please add RAL code after index number)

LED module: Philips / Osram or Tridonic LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting - index 4601 direct / indirect lighting - index 4601UD

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

General data: 5 Years standard warranty
Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used








Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	20,00
4000	Ra > 80	50.000	5	3	20,00

3000	Ra > 80	50.000	5	3	20,00
4000	Ra > 80	50.000	5	3	20,00



[AC] diffuser

[MPR] diffuser



Colour: Standard (RAL 9000, other RAL colours on request (please add RAL code after index number)

LED module: Philips / Osram or Tridonic LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting - index 3663 direct / indirect lighting - index 3663 UD

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

General data: 5 Years standard warranty
Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements, Luminous flux & Luminaire Power tolerance +/- 10%.



System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	25,00
4000	Ra > 80	50.000	5	3	25,00
3000	Ra > 80	50.000	5	3	25,00
4000	Ra > 80	50.000	5	3	25,00

[AC] diffuser

[MPR] diffuser




Colour: LED module Colour temperature: Colour Rendering Index (CRI) Driver: Emergency Movement Daylight control range: IP Class: Power: Lighting direction: Reflector type: Light distribution: General data

Colour: LED module: Philips retrofit E27 LED bulb Colour temperature: 2700K Colour Rendering Index (CRI) >80 in standard Driver: N/A Emergency unit: N/A Movement sensor: N/A Daylight control sensor: N/A Operating temperature range: 0°C ... +40°C IP Class: IP20 Power: 220-240V 50/60Hz Lighting direction: Direct lighting Reflector type: N/A Light distribution: Symmetric General data: 3 Years standard warranty Different lumen output or wattage available on request All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED efficacy improvements: Luminous flux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	4	5,90

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6519.4800/827	4800	54	2700	Ra > 80	50.000	5	4	8,90



Standard Black 5005, 001el
RAL colours on request (please
add RAL code after index
number)

Colour:

LED module: Philips retrofit E27 LED bulb

Colour temperature: 2700K

Colour Rendering Index (CRI) >80 in standard

Driver: N/A

Emergency unit: N/A

Movement sensor: N/A

Daylight control sensor: N/A

Operating temperature range: 0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: N/A

Light distribution: Symmetric

General data: 3 Years standard warranty

Different lumen output or
wattage available on request


All other technical features
such as : Luminaire Efficacy,
LOR, Lumen maintenance L/B
etc. available in our pricelist

Wattage of products may vary
due to constant LED efficacy
improvements: Luminous flux
& Luminaire Power tolerance
+/- 10%.

System power consumption
(LED module & driver) depends
on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	4	12,00



Colour:

LED module: Philips retrofit E27 LED bulb

Colour temperature: 2700K

Colour Rendering Index (CRI) >80 in standard

Driver: N/A

Emergency unit: N/A

Movement sensor: N/A

Daylight control sensor: N/A

Operating temperature range: 0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: N/A

Light distribution: Symmetric

General data: 3 Years standard warranty

Different lumen output or
wattage available on request

All other technical features
such as : Luminaire Efficacy,
LOR, Lumen maintenance L/B
etc. available in our pricelist

Wattage of products may vary
due to constant LED efficacy
improvements: Luminous flux
& Luminaire Power tolerance
+/- 10%.

System power consumption
(LED module & driver) depends
on components used

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5277.8000/827	8000	90	2700	Ra > 80	50.000	5	4	16,00

Colour: Standard Black 9005, or other RAL colours on request (please add RAL code after index number)

LED module: Philips retrofit E27 LED bulb

Colour temperature: 2700K

Colour Rendering Index (CRI) >80 in standard

Driver: N/A

Emergency unit: N/A

Movement sensor: N/A

Daylight control sensor: N/A

Operating temperature range: 0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: N/A

Light distribution: Symmetric

General data: 3 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements: Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	4	32,00



Colour:

LED module

Colour tem

Colour Ren (CRI)

Driver:

Emergency

Movement

Daylight co

Operating range:

IP Class:

Power:

Lighting di

Reflector ty

Light distri

Diffuser:

General da



250x300 V

500070E

F

CE

POWER LED



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
55416000/830E	6000	60	3000	Ra > 80	50.000	5	3	7,00
55416000/840E	6000	60	4000	Ra > 80	50.000	5	3	7,00

Colour: Standard grey, Outer HAL colours on request

LED module: Vossloh Schwabe LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP44

Power: 220-240V 50/60Hz

Lighting direction : Direct lighting

Reflector type : N/A

Light distribution : Symmetric

Diffuser : White PMMA Acrylic diffuser in standard, Micropismatic [MPR] on request

General data: 3 Years standard warranty

All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module

Colour tem

Colour Ren (CRI)

Driver:

Emergency

Movement

Daylight co

Operating range:

IP Class:

Power:

Lighting di

Reflector ty

Light distri

Diffuser:

General da



250x300 V

500070E


F

CE

POWER LED



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	5,00
4000	Ra > 80	50.000	5	3	5,00



FOE

Standard Gray 5006, Other RAL
colours on request (please add
RAL code after index number)

Philips, Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard,
DALI on request

On request - Standard or DALI 3
hour emergency unit

on request

Daylight control sensor:

Operating temperature range:

IP20 in standard, IP44 on request

2202 NV 05 1A072-022

Direct lighting

Muscinium whitei

Can a woman have an affair?

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	4,10
4000	Ra > 80	50.000	5	3	4,10



Colour:

LED module

Colour tem

Colour Ren
(CRI):

Driver:

Emergency

Movement

Daylight co

Operating range:

IP Class:

Power:


Lighting design

Deflection (mm)

11-14-44

Diffuser:

General data



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [years]	MacAdam [SDCM]	Weight [kg]
4882.8800/830	8800	58	3000	Ra > 80	50.000	5	3	9,50
4882.8800/840	8800	58	4000	Ra > 80	50.000	5	3	9,50
4882.11000/830	11000	74	3000	Ra > 80	50.000	5	3	13,00
4882.11000/840	11000	74	4000	Ra > 80	50.000	5	3	13,00

Standard Gray 5006, Other RAL
colours on request (please add
RAL code after index number)

Philips, Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver in standard,
DALI on request

On request - Standard or DALI 3
hour emergency unit

on request

on request

0°C...+40°C

IP20 in standard, **IP44** on request

220-240V 50/60Hz

Direct lighting

Aluminium white

Symmetric

White acrylic diffuser [WD] in standard, acrylic frosted [AC], microprismatic [MPR] or any other on request.

5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module

Colour tem

Colour Ren
(CRI):

Driver:

Emergency

Movement

Daylight co

Operating range:

IPClass:

Power:

Lighting design

Reflector tv

Light distri


Diffuser:

General data



Colour temp. [K]	CRI	Lifetime [h]	Warranty [years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50,000	5	3	4,50
4000	Ra > 80	50,000	5	3	4,50

Index.no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [years]	MacAdam [SDCM]	Weight [kg]
6103:10400/830	10400	68	3000	Ra > 80	50.000	5	3	8,00
6103:10400/840	10400	68	4000	Ra > 80	50.000	5	3	8,00





Colour: Standard White 5000, cooler RAL colours on request (please add RAL code after index number)

LED module: Philips / Osram or Tridonic LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

General data: 5 Years standard warranty

Body of the luminaire is made of perforated steel filled with Acoustic Foam



Luminaire can be connected into lighting lines, blind sections available on request



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	30,00
4000	Ra > 80	50.000	5	3	30,00



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3372.2200/827	2200	18	2700	Ra > 80	50.000	5	3	4,80
3372.2200/830	2200	18	3000	Ra > 80	50.000	5	3	4,80
3372.2200/840	2200	18	4000	Ra > 80	50.000	5	3	4,80
3372.4800/827	4800	40	2700	Ra > 80	50.000	5	3	4,80
3372.4800/830	4800	40	3000	Ra > 80	50.000	5	3	4,80
3372.4800/840	4800	40	4000	Ra > 80	50.000	5	3	4,80
3372.6400/827	6400	56	2700	Ra > 80	50.000	5	3	4,80
3372.6400/830	6400	56	3000	Ra > 80	50.000	5	3	4,80
3372.6400/840	6400	56	4000	Ra > 80	50.000	5	3	4,80





Colour: Standard White 5000, other RAL colours on request (please add RAL code after index number)

LED module: Philips / Osram or Tridonic LED module included

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI) >80 in standard

Driver: Electronic driver in standard, DALI on request

Emergency unit: On request - Standard or DALI 3 hour emergency unit

Movement sensor: on request

Daylight control sensor: on request

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: Aluminium white

Light distribution: Symmetric

Diffuser: White acrylic diffuser (WD) in standard, acrylic frosted (AC), microprismatic (MPR) or any other on request.

General data: 5 Years standard warranty



IP20	220-240 V 50/60 Hz				CE			POWER LVS			
Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]			
6524.5000/830	5000	38	3000	Ra > 80	50.000	5	3	12,00			
6524.5000/840	5000	38	4000	Ra > 80	50.000	5	3	12,00			


Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements; Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

		POWER LVS			CE			CE	IP20	220-240 V 50/60 Hz	6524.5000/830	5000	38	3000	Ra > 80	50.000	5	4	8,00
Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]														
3000	Ra > 80	50.000	5	4	8,00														
4000	Ra > 80	50.000	5	4	8,00														





Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:
Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

General data:

Colour on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K available

>80 or >90 in standard

Electronic driver in standard, DALI on request

On request - Standard or DALI 3 hour emergency unit

N/A

N/A

0°C... +40°C

IP44

220-240V 50/60Hz

Direct lighting

Aluminium white

Symmetric

5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour:

LED module:

Colour tem

Colour Ren (CRI)

Driver:

Emergency

Movement

Daylight co

Operating range:

IP Class:

Power:

Lighting di

Reflector ty

Light distri


Diffuser:

General da



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	15,00
4000	Ra > 80	50.000	5	3	15,00
3000	Ra > 80	50.000	5	3	15,00
4000	Ra > 80	50.000	5	3	15,00

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4404.3200/827	3200	28	2700	Ra > 80	50.000	5	3	9,00
4404.3200/830	3200	28	3000	Ra > 80	50.000	5	3	9,00
4404.3200/840	3200	28	4000	Ra > 80	50.000	5	3	9,00
4404.4500/830	4500	34	3000	Ra > 80	50.000	5	3	9,00
4404.4500/840	4500	34	4000	Ra > 80	50.000	5	3	9,00
4404.3000/927	3000	32	2700	Ra > 90	50.000	5	3	9,00
4404.3000/930	3000	32	3000	Ra > 90	50.000	5	3	9,00
4404.3000/940	3000	32	4000	Ra > 90	50.000	5	3	9,00
4404.4500/927	4500	34	2700	Ra > 90	50.000	5	3	9,00
4404.4500/930	4500	34	3000	Ra > 90	50.000	5	3	9,00
4404.4500/940	4500	34	4000	Ra > 90	50.000	5	3	9,00
4404.3000/930CW	3000	36	3000	Ra > 90	50.000	5	3	9,00
4404.3800/930CW	3800	43	3000	Ra > 90	50.000	5	3	9,00
4404.3000/925FW	3000	44	2500	Ra > 90	50.000	5	3	9,00
4404.3000/930FR	3000	42	3000	Ra > 90	50.000	5	3	9,00



315



Colour: [View all colours on request](#) (please add RAL code after index number)

LED module:
Colour temperature:
2700K, 3000K or 4000K available

Colour Rendering Index (CRI)
Driver:
Electronic driver in standard, DALI on request

Movement sensor:
On request - Standard or DALI 3 hour emergency unit

Daylight control sensor:
N/A

Operating temperature range:
N/A

IP Class:
0°C ... +40°C

Power:
IP20 in standard, IP44 on request

Lighting direction:
220-240V 50/60Hz

Reflector type:
Direct lighting

Light distribution:
Aluminium white

Diffuser:
Symmetric

General data:
Clear or frosted acrylic on request

5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

Product is also available with special application LED modules: Premium Color, CrispWhite,

Food WarmWhite, Food PremiumRed and many others - details on request


All other technical features such as: Luminare Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminare Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	3	14,00
3000	Ra > 80	50.000	5	3	14,00
4000	Ra > 80	50.000	5	3	14,00
3000	Ra > 80	50.000	5	3	14,00
4000	Ra > 80	50.000	5	3	14,00
2700	Ra > 90	50.000	5	3	14,00
3000	Ra > 90	50.000	5	3	14,00
4000	Ra > 90	50.000	5	3	14,00
2700	Ra > 90	50.000	5	3	14,00
3000	Ra > 90	50.000	5	3	14,00
4000	Ra > 90	50.000	5	3	14,00
2700	Ra > 90	50.000	5	3	14,00
3000	Ra > 90	50.000	5	3	14,00
4000	Ra > 90	50.000	5	3	14,00
2500	Ra > 90	50.000	5	3	14,00
3000	Ra > 90	50.000	5	3	14,00








Colour:
LED modul
Colour tem
Colour Ren
(CRI)
Driver:
Emergency
Movement
Daylight co
Operating r
ange:
IP Class:
Power:
Lighting di
Reflector t
Light distri
General da

Standard CRI 90,00, other RAL
colours on request (please add
RAL code after index number)
Philips / Osram or Tridonic LED
module included
3000K or 4000K
>80 in standard
Electronic integrated driver in
standard, DALI on request
N/A
N/A
N/A
0°C... +40°C
IP20 in standard, IP44 on
request
220-240V 50/60Hz
Direct lighting
Acrylic
Symmetric
5 Years standard warranty,
possible extension with project
registration
Different lumen output or
wattage available on request
All other technical features
such as : Luminaire Efficacy,
LOR, Lumen maintenance L/B
etc. available in our pricelist
Wattage of products may vary
due to constant LED efficacy
improvements. Luminous flux
& Luminaire Power tolerance
+/- 10%.
System power consumption
(LED module & driver) depends
on components used

Colour:
LED module:
Colour temperature:
Colour Rendering Index
(CRI)
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature
range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
With integrated AC driver								
5284.1100/830	1100	10	3000	Ra > 80	50.000	5	3	3,60
5284.1100/840	1100	10	4000	Ra > 80	50.000	5	3	3,60
5284.2000/830	2000	18	3000	Ra > 80	50.000	5	3	3,60
5284.2000/840	2000	18	4000	Ra > 80	50.000	5	3	3,60
5284.3000/830	3000	27	3000	Ra > 80	50.000	5	3	3,60
5284.3000/840	3000	27	4000	Ra > 80	50.000	5	3	3,60
With AC/DC driver								
3495.1100/830	1100	12	3000	Ra > 80	50.000	5	3	4,20
3495.1100/840	1100	12	4000	Ra > 80	50.000	5	3	4,20
3495.2000/830	2000	20	3000	Ra > 80	50.000	5	3	4,20
3495.2000/840	2000	20	4000	Ra > 80	50.000	5	3	4,20
3495.3200/830	3200	31	3000	Ra > 80	50.000	5	3	4,20
3495.3200/840	3200	31	4000	Ra > 80	50.000	5	3	4,20



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	2,30
4000	Ra > 80	50.000	5	3	2,30
3000	Ra > 80	50.000	5	3	2,30
4000	Ra > 80	50.000	5	3	2,30





Colour:

LED module:

Colour temperature:

Colour Rendering Index (CRI)

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

General data:

Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
------------------	-----	--------------	------------------	----------------	-------------

3000	Ra > 80	50.000	5	3	4,50
4000	Ra > 80	50.000	5	3	4,50
3000	Ra > 80	50.000	5	3	4,50
4000	Ra > 80	50.000	5	3	4,50
3000	Ra > 80	50.000	5	3	4,50
4000	Ra > 80	50.000	5		4,50
3000	Ra > 80	50.000	5	3	5,10
4000	Ra > 80	50.000	5	3	5,10
3000	Ra > 80	50.000	5	3	5,10
4000	Ra > 80	50.000	5	3	5,10
3000	Ra > 80	50.000	5	3	5,10
4000	Ra > 80	50.000	5	3	5,10

Standard CRI 90,00, other RAL colours on request (please add RAL code after index number)

Philips / Osram or Tridonic LED module included

3000K or 4000K

>80 in standard

Electronic driver or electronic integrated, DALI on request

On request

N/A

N/A

0°C ... +40°C

IP20 in standard, IP44 on request

220-240V 50/60Hz

Direct Lighting

Acrylic

Symmetric


5 Years standard warranty, possible extension with project registration

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used




Colour: LED module Colour temperature Colour Rendering Index (CRI) Driver: Emergency Movement Daylight colour range: IP Class: Power: Lighting distribution Reflector type Light distribution General data



Colour: Philips / Osram or Tridonic LED module included Colour temperature: 3000K or 4000K Colour Rendering Index (CRI): >80 in standard Driver: Electronic driver or electronic integrated, DALI on request Emergency unit: On request Movement sensor: N/A Daylight control sensor: N/A Operating temperature range: 0°C ... +40°C IP Class: IP20 in standard, IP44 on request Power: 220-240V 50/60Hz Lighting direction: Direct lighting Reflector type: Aluminium white Light distribution: Symmetric General data: 5 Years standard warranty, possible extension with project registration Different lumen output or wattage available on request All other technical features such as: Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%. System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5213.1000/927	1000	11	2700 K	Ra > 80	25.000	3	4	3,50
5213.1500/927	1500	15	2700 K	Ra > 80	25.000	3	4	3,50





Colour:
LED module
Colour tem
Colour Ren
(CRI):
Driver:
Emergency
Movement
Daylight co
Operating r
range:
IP Class:
Power:
Lighting di
Reflector t
Light distri
Reflector b
General da



Colour:
LED module:
Colour temperature:
Colour Rendering Index (CRI)
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:

Philips / Osram or Tridonic LED module included
3000K, 4000K or 5000K available
>80 in standard
Electronic driver in standard, DALI on request
N/A
N/A
N/A
0°C ... +40°C
IP20 in standard, IP44 on request
220-240V 50/60Hz
Direct lighting
Aluminium silver
Symmetric
5 Years standard warranty, possible extension with project registration


Different lumen output or wattage available on request
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used

Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00
5000	Ra > 80	50.000	5	3	10,00



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	15.000	3	4	1,50
4000	Ra > 80	15.000	3	4	1,50
5000	Ra > 80	15.000	3	4	1,50



98



Colour:
LED module:
Colour tem:
Colour Rend (CRI):
Driver:
Emergency:
Movement:
Daylight co:
Operating range:
IP Class:
Power:
Lighting di:
Reflector ty:
Light distri:
Reflector b:
General da:




Colour:
LED module:
Colour temperature:
Colour Rendering Index (CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
Reflector beam angle:
General data:

Philips LED module included
3000K or 4000K available
>80 or >90 in standard
Electronic integrated driver
N/A
N/A
N/A
0°C ... +40°C
IP20
220-240V 50/60Hz
Direct lighting
Aluminium glossy
Symmetric
16° / 24° / 36° / 54°
5 Years standard warranty
All other technical features such as: Luminaires Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaires Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5849.355/827/36D	355	4,6	2700	Ra > 80	15.000	3	4	1,20
5849.370/830/36D	370	4,6	3000	Ra > 80	15.000	3	4	1,20
5849.390/840/36D	390	4,6	4000	Ra > 80	15.000	3	4	1,20

Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	1,40
3000	Ra > 90	50.000	5	3	1,40
4000	Ra > 80	50.000	5	3	1,40
3000	Ra > 80	50.000	5	3	1,40
3000	Ra > 90	50.000	5	3	1,40
4000	Ra > 80	50.000	5	3	1,40
3000	Ra > 80	50.000	5	3	1,40
3000	Ra > 90	50.000	5	3	1,40
4000	Ra > 80	50.000	5	3	1,40



Colour:
LED module
Colour tem
Colour Ren
(CRI):
Driver:
Emergency
Movement
Daylight co
Operating
range:
IP Class:
Power:
Lighting di
Reflector t
Light distri
General da




Colour:
LED module:
Colour temperature:
Colour Rendering Index (CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
Diffuser:
General data:

Standard Gray 3000, other RAL colours on request (please add RAL code after index number)
Philips, Osram or Tridonic LED module included
3000K or 4000K
>80 in standard
Electronic driver in standard, DALI on request
N/A
N/A
N/A
0°C... +40°C
IP20
220-240V 50/60Hz
Direct lighting
Aluminium
Symmetric
Clear or frosted glass on request
5 Years standard warranty
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance, L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used




Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	2,90
4000	Ra > 80	50.000	5	3	2,90
3000	Ra > 80	50.000	5	3	2,90
4000	Ra > 80	50.000	5	3	2,90
3000	Ra > 80	50.000	5	3	2,90
4000	Ra > 80	50.000	5	3	2,90

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3787.610/827/24D	610	10	2700	Ra > 80	40.000	3	3	1,50
3787.610/830/40D	610	10	3000	Ra > 80	40.000	3	3	1,50
3787.800/827/24D	800	15	2700	Ra > 80	40.000	3	3	1,50
3787.760/827/40D	760	15	2700	Ra > 80	40.000	3	3	1,50



205



Colour: **LED module:** LED GU10 retrofit lamp included

Colour temperature: 2700K, 3000K or 4000K available

Colour Rendering Index (CRI): >80 in standard, other on request

Driver: N/A

Emergency unit: N/A

Movement sensor: N/A

Daylight control sensor: N/A

Operating temperature range: 0°C ... +40°C

IP Class: IP20 in standard, IP44 on request

Power: 220-240V 50/60Hz

Lighting direction: Direct lighting

Reflector type: N/A

Light distribution: Symmetric

Reflector beam angle: 36° other on request

General data: 3 Years standard warranty

Different lumen output or wattage available on request


All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	15.000	3	4	0,40
3000	Ra > 80	15.000	3	4	0,40
4000	Ra > 80	15.000	3	4	0,40



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4587800/827	800	10	2700	Ra > 80	50.000	5	3	0,80
4587800/830	800	10	3000	Ra > 80	50.000	5	3	0,80
4587800/840	800	10	4000	Ra > 80	50.000	5	3	0,80



Colour: .

LED module

Colour tem

Colour Ren (CRI):

Driver:

Emergency

Movement

Daylight co

Operating range:

IP Class:

Power:

Lighting di

Reflector ty

Light distri

General da



Colour: .

LED module:

Colour temperature:

Colour Rendering Index (CRI):

Driver:

Emergency unit:

Movement sensor:

Daylight control sensor:

Operating temperature range:

IP Class:

Power:

Lighting direction:

Reflector type:

Light distribution:

General data:

LED module included

2700K, 3000K or 4000K available

>80 in standard

Electronic integrated driver

N/A

N/A

N/A

0°C ... +40°C

IP20

220-240V 50/60Hz

Direct lighting

Aluminium


Symmetric

5 Years standard warranty

All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelist


Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.

System power consumption (LED module & driver) depends on components used



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	3	1,50
3000	Ra > 80	50.000	5	3	1,50
4000	Ra > 80	50.000	5	3	1,50

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3771800/827	800	10	2700	Ra > 80	50.000	5	3	0,60
3771800/830	800	10	3000	Ra > 80	50.000	5	3	0,60
3771800/840	800	10	4000	Ra > 80	50.000	5	3	0,60



Colour:
LED module
Colour tem
Colour Ren
(CRI):
Driver:
Emergency
Movement
Daylight co
Operating r
range:
IP Class:
Power:
Lighting di
Reflector t
Light distri
General da




Standard Gray 3000, other RAL
colours on request (please add
RAL code after index number)
Philips / Osram or Tridonic LED
module
2700K, 3000K or 4000K
>80 in standard, other on
request
Electronic driver in standard,
DALI on request
N/A
N/A
N/A
0°C... +40°C
IP20
220-240V 50/60Hz
Direct lighting
Aluminium glossy
Symmetric
5 Years standard warranty
All other technical features
such as : Luminaire Efficacy,
LOR, Lumen maintenance L/B
etc. available in our pricelist
Wattage of products may vary
due to constant LED efficacy
improvements. Luminous flux
& Luminaire Power tolerance
+/- 10%.

Colour:
LED module:
Colour temperature:
Colour Rendering Index
(CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature
range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:




Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
2700	Ra > 80	50.000	5	3	10,00
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00
2700	Ra > 80	50.000	5	3	10,00
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00
2700	Ra > 80	50.000	5	3	10,00
3000	Ra > 80	50.000	5	3	10,00
4000	Ra > 80	50.000	5	3	10,00

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
49071100/827	1100	9	2700	Ra > 80	50.000	5	3	12,00
49071100/830	1100	9	3000	Ra > 80	50.000	5	3	12,00
49071100/840	1100	9	4000	Ra > 80	50.000	5	3	12,00
49072400/827	2400	20	2700	Ra > 80	50.000	5	3	12,00
49072400/830	2400	20	3000	Ra > 80	50.000	5	3	12,00
49072400/840	2400	20	4000	Ra > 80	50.000	5	3	12,00
49073200/827	3200	28	2700	Ra > 80	50.000	5	3	12,00
49073200/830	3200	28	3000	Ra > 80	50.000	5	3	12,00
49073200/840	3200	28	4000	Ra > 80	50.000	5	3	12,00





Colour:
LED module
Colour temperature
Colour Rendering Index (CRI):
Driver:
Emergency
Movement
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:



Standard CRI 9000, other RAL colours on request (please add RAL code after index number)
Osram LED module
3000K or 4000K
>80 in standard, other on request
Electronic integrated driver
N/A
N/A
N/A
0°C ... +40°C
IP20
220-240V 50/60Hz
Direct lighting
Integrated lens
Symmetric
5 Years standard warranty
All other technical features such as : Luminaire Efficacy LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.
System power consumption (LED module & driver) depends on components used


Colour:
LED module:
Colour temperature:
Colour Rendering Index (CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:



Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5935.1500/E27	1500	15	2700	Ra > 80	25.000	3	4	4,50



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	35.000	5	4	1,50
4000	Ra > 80	35.000	5	4	1,50
3000	Ra > 80	35.000	5	4	1,50
4000	Ra > 80	35.000	5	4	1,50





Colour:
LED module
Colour tem
Colour Ren
(CRI)
Driver:
Emergency
Movement
Daylight co
Operating r
range:
IP Class:
Power:
Lighting di
Reflector t
Light distri
General da


Standard white RAL 9016,
other RAL colours on request
(please add RAL code after
index number)
Philips MASTER LEDtube
retrofit LED lamp
3000K, 4000K or 6500K
>80 in standard
N/A
N/A
N/A
N/A
0°C... +40°C
IP20
220-240V 50/60Hz
Direct lighting
N/A
Symmetric
5 Years standard warranty
Different lumen output or
wattage available on request
All other technical features
such as : Luminaire Efficacy,
LOR, Lumen maintenance L/B
etc. available in our pricelist
Wattage of products may vary
due to constant LED efficacy
improvements. Luminous flux
& Luminaire Power tolerance
+/- 10%.

Colour:
LED module:
Colour temperature:
Colour Rendering Index
(CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature
range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Length [mm]	Weight [kg]
3000K	Ra > 80	50.000	5	3	1296	2,00
4000K	Ra > 80	50.000	5	3	1296	2,00
6500K	Ra > 80	50.000	5	3	1296	2,00
3000K	Ra > 80	50.000	5	3	1596	3,00
4000K	Ra > 80	50.000	5	3	1596	3,00
6500K	Ra > 80	50.000	5	3	1596	3,00

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
6526,1500/827	1500	15	2700	Ra > 80	25.000	3	4	3,00








Læsesal

K2 01
Læsesal

Colour:
LED module
Colour tem
Colour Ren
(CRI):
Driver:
Emergency
Movement
Daylight co
Operating
range:
IP Class:
Power:
Lighting di
Reflector ty
Light distri
General da



Standard Gray 3000, other RAL colours on request (please add RAL code after index number)
Philips / Osram or Tridonic LED module
3000K or 4000K
>80 in standard, other on request
Electronic driver in standard, DALI on request
N/A
N/A
N/A
0°C... +40°C
IP20
220-240V 50/60Hz
Direct lighting
Aluminium glossy
Symmetric
5 Years standard warranty
All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist
Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.


Colour:
LED module:
Colour temperature:
Colour Rendering Index (CRI):
Driver:
Emergency unit:
Movement sensor:
Daylight control sensor:
Operating temperature range:
IP Class:
Power:
Lighting direction:
Reflector type:
Light distribution:
General data:




Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
4262 2400/827/24D	2400	45	2700	Ra > 80	40.000	3	3	5,50
4262 2280/827/40D	2280	45	2700	Ra > 80	40.000	3	3	5,50



Colour temp. [K]	CRI	Lifetime [H]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	4	1,50
4000	Ra > 80	50.000	5	4	1,50





Colour: **LED module:** Philips, Osram or Tridonic LED modules

Colour temperature: 3000K or 4000K

Colour Rendering Index (CRI): >80 in standard

Driver: Electronic driver in standard

Emergency unit: N/A

Movement sensor: N/A

Daylight control sensor: N/A

Operating temperature range: 0°C ... +40°C

IP Class: IP20

Power: 220-240V 50/60Hz

Lighting direction: Indirect lighting

Reflector type: Aluminium white

Light distribution: Symmetric

General data: 5 Years standard warranty

Different lumen output or wattage available on request

All other technical features such as : Luminaire Efficacy, LOR, Lumen maintenance L/B etc. available in our pricelist

Wattage of products may vary due to constant LED efficacy improvements. Luminous flux & Luminaire Power tolerance +/- 10%.



Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
3000	Ra > 80	50.000	5	3	8,00
4000	Ra > 80	50.000	5	3	8,00

Index no.	Lumen output [lm]	Power [W]	Colour temp. [K]	CRI	Lifetime [h]	Warranty [Years]	MacAdam [SDCM]	Weight [kg]
5359 710/827	710	9,2	2700	Ra > 80	15.000	3	4	1,90
5359 740/830	740	9,2	3000	Ra > 80	15.000	3	4	1,90
5359 780/840	780	9,2	4000	Ra > 80	15.000	3	4	1,90

